

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq floorvarnish X10  
Revision date : 08.07.2014  
Date of print : 16-09-2014

Version (Revision) : 2.0.0 (1.0.0)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Lacq floorvarnish X10 (6300)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses**

**Product categories [PC]**

PC9A - Coatings and paints, thinners, paint removers

### 1.3 Details of the supplier of the safety data sheet

**Supplier (manufacturer/importer/only representative/downstream user/distributor)**

Vliegenthart B.V.

**Street :** Zuiderhavenweg 42

**Postal code/city :** 4004 JJ TIEL

**Telephone :** +31 (0)344 63 33 36

**Telefax :** +31 (0)344 63 16 16

### 1.4 Emergency telephone number

+31 (0)344 63 33 36 (During officehours: 08:30 - 17:00 hour.)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification according to Directive 67/548/EEC or 1999/45/EC**

Flammable. · Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · Vapours may cause drowsiness and dizziness.

R 10 · N ; R 51/53 · R 67 · R 66

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Category 2 ; Toxic to aquatic life with long lasting effects.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - Specific target organ toxicity (single exposure) : Category 3 ; May cause drowsiness or dizziness.

### 2.2 Label elements

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



Flame (GHS02) · Environment (GHS09) · Exclamation mark (GHS07)

**Signal word**

Warning

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

### Hazard statements

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233 Keep container tightly closed.  
P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container to chemicals waste depot.

### Supplemental Hazard information (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3 Other hazards

None

## SECTION 3: Composition/ information on ingredients

### 3.2 Mixtures

#### Hazardous ingredients

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; REACH registration No. : 01-2119458049 ; EC No : 919-446-0; CAS No. : 64742-82-1

Weight fraction : 25 - 50 %  
Classification 67/548/EEC : R10 N ; R51/53 Xn ; R65 R67 R66  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS ; REACH registration No. : 01-2119463258-33 ; EC No : 919-857-5

Weight fraction : 10 - 25 %  
Classification 67/548/EEC : R10 Xn ; R65 R67 R66  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336

TERPINEOL ; REACH registration No. : 01-2119553062-49 ; EC No : 232-268-1; CAS No. : 8000-41-7

Weight fraction : 1 - 2,5 %  
Classification 67/548/EEC : Xi ; R36/38  
Classification 1272/2008 [CLP] : Skin Irrit. 2 ; H315 Eye Irrit. 2 ; H319

HYDROCARBONS - TERPENE ; REACH registration No. : 01-2119980606-28 ; EC No : 273-309-3; CAS No. : 68956-56-9

Weight fraction : 0,1 - 1 %  
Classification 67/548/EEC : R10 N ; R51/53 R43 Xn ; R65 Xi ; R36/38  
Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 Skin Irrit. 2 ; H315 Skin Sens. 1 ; H317 Aquatic Chronic 2 ; H411

2-BUTANONE OXIME ; REACH registration No. : 01-2119539477-28 ; EC No : 202-496-6; CAS No. : 96-29-7

Weight fraction : < 1 %  
Classification 67/548/EEC : Carc. Cat.3 ; R40 R43 Xi ; R41 Xn ; R21  
Classification 1272/2008 [CLP] : Carc. 2 ; H351 Eye Dam. 1 ; H318 Acute Tox. 4 ; H312 Skin Sens. 1 ; H317

2-ETHYLHEXANOIC ACID, MANGANESE SALT ; REACH registration No. : 01-2119979087-23 ; EC No : 240-085-3; CAS No. : 15956-58-8

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014  
**Version (Revision) :** 2.0.0 (1.0.0)

Weight fraction : < 2,5 %  
Classification 67/548/EEC : Repr. Cat.3 ; R63 N ; R51/53 Xn ; R48/20/22 Xi ; R36  
Classification 1272/2008 [CLP] : Repr. 2 ; H361d STOT RE 2 ; H373 Eye Irrit. 2 ; H319 Aquatic Chronic 2 ; H411

### Additional information

Full text of R-, H- and EUH-phrases: see section 16.

### 3.3 Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

If breathing is irregular or stopped, administer artificial respiration.

#### In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Do not wash with: Solvents/Thinner

#### After eye contact

If possible, remove contactlenses. In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

#### After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do not induce vomiting. Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

None

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Alcohol resistant foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Sand. Water mist

#### Unsuitable extinguishing media

High power water jet.

### 5.2 Special hazards arising from the substance or mixture

#### Hazardous combustion products

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### 5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

### 5.4 Additional information

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

Burning produces heavy smoke. Do not allow run-off from fire-fighting to enter drains or water courses. Use water spray jet to protect personnel and to cool endangered containers.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Wear breathing apparatus if exposed to vapours/dusts/aerosols. See protective measures under point 7 and 8.

#### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

##### For cleaning up

Treat the recovered material as prescribed in the section on waste disposal. Clean with detergents. Avoid solvent cleaners.

#### 6.4 Reference to other sections

None

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling



##### Protective measures

Only use the material in places where open light, fire and other flammable sources can be kept away. Wear personal protection equipment. (see chapter 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Avoid the forming of inflammable or explosive concentrations of vapour in the air and exposure concentrations higher than permitted, Comply with the health and safety at work laws.

##### Fire prevent measures

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours can form explosive mixtures with air.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Technical measures and storage conditions

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access.

##### Requirements for storage rooms and vessels

Keep container tightly closed. Ensure adequate ventilation of the storage area. Restrict access to stockrooms.

##### Hints on joint storage

###### Keep away from

Keep away from ignition sources. Keep away from oxidizing agents, from strongly alkaline and strongly acid materials. Always keep in containers of same material as the original one. See also instructions on the label. Avoid

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

heating and direct sunlight.

## 7.3 Specific end use(s)

None

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

None

### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

#### Personal protection equipment

##### Eye / face protection



Eye glasses with side protection

##### Skin protection

###### Hand protection



Long Gloves NR (natural rubber, natural latex) Recommended Thickness DIN EN 374

##### Body protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

**Suitable protective clothing :** Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

##### Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. By spraying: air fed respirator. By other operations than spraying: in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**Colour :** brown

**Odour :** Characteristic.

**Odor Threshold value** Not determined

#### Safety relevant basis data

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq floorvarnish X10  
Revision date : 08.07.2014  
Date of print : 16-09-2014

Version (Revision) : 2.0.0 (1.0.0)

Physical state :			liquid	
Melting point / melting range :			No data available	
Boiling temperature / boiling range :	( 1013 hPa )		150	°C
Decomposition temperature :	( 1013 hPa )		Not determined	
Evaporation rate			Not determined	
Flash point :			41	°C CC
Ignition temperature :			Not determined	
Flammability (gas, solid)			Not determined	
Lower explosion limit :			0,6	Vol-%
Upper explosion limit :			8	Vol-%
Explosive properties			Not determined	
Vapour pressure :	( 50 °C )	<	1000	hPa
Density :	( 20 °C )	ca.	0,904	g/cm <sup>3</sup>
Water solubility :	( 20 °C )		insoluble	
PH value :			not applicable	
Flow time :	( 23 °C )	>	100	s DIN-cup 4 mm
Viscosity :	( 20 °C )		5 - 9	mPa.s
Oxidising properties			Not determined	
Partition coefficient n-octanol/water			Not determined	

## 9.2 Other information

None

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No information available.

### 10.2 Chemical stability

No information available.

### 10.3 Possibility of hazardous reactions

No information available.

### 10.4 Conditions to avoid

Stable under recommended storage and handling conditions(See section 7 and 8).

### 10.5 Incompatible materials

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute effects

##### Acute oral toxicity

Parameter :

LD50 ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

Exposure route : (2-25%) ; CAS No. : 64742-82-1 )  
Oral  
Species : Rat  
Effective dose : > 15000 mg/kg

### Acute dermal toxicity

Parameter : LD50 ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1 )  
Exposure route : Dermal  
Species : Rabbit  
Effective dose : > 3400 mg/kg

### Acute inhalation toxicity

Parameter : LC50 ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1 )  
Exposure route : Inhalation  
Species : Rat  
Effective dose : > 13,1 mg/l  
Exposure time : 4 h

### 11.3 Other adverse effects

Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea. Delayed reactions possible (breathing problems, coughs, asthma) Eye contact: irritation. Inhalation/eye contact: in high concentrations irritating to the mucous membranes, narcotic effect and influence on power of reaction and loss of coordination possible.

### 11.4 Additional information

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity

##### Acute (short-term) fish toxicity

Parameter : LC50 ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1 )  
Species : Oncorhynchus mykiss (Rainbow trout)  
Evaluation parameter : Acute (short-term) fish toxicity  
Effective dose : 10 - 30 mg/l  
Exposure time : 96 h

##### Acute (short-term) daphnia toxicity

Parameter : EC50 ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1 )  
Species : Chronic (long-term) daphnia toxicity  
Evaluation parameter : Chronic (long-term) daphnia toxicity  
Effective dose : 10 - 22 mg/l  
Exposure time : 48 h

##### Acute (short-term) algae toxicity

Parameter : EC50 ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1 )  
Species : Algae

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

Effective dose : 4,6 - 10 mg/l  
Exposure time : 72 h

#### Chronic (long-term) algae toxicity

Parameter : NOEC ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) ; CAS No. : 64742-82-1 )

Species : Algae  
Effective dose : 0,22 mg/l  
Exposure time : 72 h

#### 12.2 Persistence and degradability

No information available.

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

No information available.

#### 12.6 Other adverse effects

No information available.

#### 12.7 Further ecological information

##### Additional information

Product should not be released into water without pre-treatment (biological sewage plant).

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Product/Packaging disposal

##### Waste treatment options

##### Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. The generation of waste should always as far as possible be avoided, or be limited to a minimum. Disposal of this product, solutions and any by-products should at all times be in accordance with applicable legislation in the field of environmental protection and waste disposal legislation and any other regional or local regulations.

### SECTION 14: Transport information

#### 14.1 UN number

UN 1263

#### 14.2 UN proper shipping name

##### Land transport (ADR/RID)

PAINT RELATED MATERIAL

##### Sea transport (IMDG)

PAINT RELATED MATERIAL ( HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%) · HYDROCARBONS - TERPENE · DIPENTENE )

##### Air transport (ICAO-TI / IATA-DGR)



# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Lacq floorvarnish X10  
Revision date : 08.07.2014  
Date of print : 16-09-2014

Version (Revision) : 2.0.0 (1.0.0)

PAINT RELATED MATERIAL

## 14.3 Transport hazard class(es)

### Land transport (ADR/RID)

Class(es) : 3  
Classification code : F1  
Hazard identification number (Kemler No.) : 30  
Tunnel restriction code : D/E  
Special provisions : 640E · LQ 7 · E 1  
Hazard label(s) : 3 / N

### Sea transport (IMDG)

Class(es) : 3  
EmS-No. : F-E / S-E  
Special provisions : LQ 5 I · E 1  
Hazard label(s) : 3 / N

### Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3  
Special provisions : E 1  
Hazard label(s) : 3

## 14.4 Packing group

III

## 14.5 Environmental hazards

Land transport (ADR/RID) : Yes  
Sea transport (IMDG) : Yes (P)  
Air transport (ICAO-TI / IATA-DGR) : Yes

## 14.6 Special precautions for user

None

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

## SECTION 16: Other information

### 16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling (67/548/EEC or 1999/45/EC) · 03. Hazardous ingredients · 14. UN proper shipping name - Land transport (ADR/RID) · 14. UN proper shipping name - Sea transport (IMDG) · 14. UN proper shipping name - Air transport (ICAO-TI / IATA-DGR) · 14. Transport hazard class(es) - Land transport (ADR/RID) · 14. Transport hazard class(es) - Sea transport (IMDG) · 14. Transport hazard class(es) - Air transport (ICAO-TI / IATA-DGR)

# Safety Data Sheet

## according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

### 16.2 Abbreviations and acronyms

None

### 16.3 Key literature references and sources for data

None

### 16.5 Relevant R-, H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H227	Combustible liquid.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
10	Flammable.
21	Harmful in contact with skin.
36	Irritating to eyes.
36/38	Irritating to eyes and skin.
40	Limited evidence of a carcinogenic effect.
41	Risk of serious damage to eyes.
43	May cause sensitization by skin contact.
48/20/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
63	Possible risk of harm to the unborn child.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

### 16.6 Training advice

Make sure that employees are aware of the safety risk. People wearing breathing apparatus must be appropriately trained.

### 16.7 Additional information

The details in this material safety data sheet satisfy national and EC legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Trade name :** Lacq floorvarnish X10  
**Revision date :** 08.07.2014  
**Date of print :** 16-09-2014

**Version (Revision) :** 2.0.0 (1.0.0)

---