



## Lacq RapidOil 2C

Lacq RapidOil 2C is a product consisting of 2 components. Component A is based on vegetable oil and is completely solvent-free. With only a single coat gives you the wood color and the protection it deserves. With adding the solvent free accelerator (component B) accelerates you the drying of the oil causing the treated surface to load faster is. The A component can also be used as a renovation or maintenance oil on surfaces previously treated with RapidOil.

### Applicable on interior wood:

- Parquet
- Wooden tabletops
- Wooden kitchen surfaces
- Other interior wood

Lacq RapidOil 2C is resistant to water, so it is also suitable for bathrooms and kitchens. It colors and protects in one layer. It has a high penetration in substrate, which makes the wood of protected from the inside. In addition, the product consists of more than 95% renewable raw materials and provide lasting protection.

### Processing:

1. Untreated wood: sand the surface according to the rules of the wood. Use do not use a finer grit than 120. Please note that sanding marks and irregularities will be extra noticeable after applying the oil. Vacuum thoroughly after sanding and remove all dust residues.
2. Mix the A and B Component carefully and stir the mixture well for 2 minutes.
3. Make sure that the surface to be treated is dry. Bring a small one amount of Lacq RapidOil 2C and spread it with a cloth or polishing machine with thin beige pad. Work in areas of 5 - 10 m<sup>2</sup>.
4. Let Rapidoil 2C act for a few minutes. Then remove all excess oil within 15 minutes per zone. Use a cloth or polisher with a white pad for this. The surface must feel dry to the touch! Finish all zones in the same way.
5. In a well-ventilated area, the surface can be cleaned after 24 - 36 hours after the treatment taxed. After 5 days the surface can be cleaned and maintained with Lacq Nourishing Floor Soap.

*Pay attention! The product is ready to use, so do not dilute it! After mixing maximum 4 - 6 hours processable (depending on temperature and humidity).*

*Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.*

### Coverage:

About 30-50 m<sup>2</sup> per liter.

*Pay attention! Efficiency always depends on the structure, suction of the wood, the thickness of the layer, the tools used and the conditions of application.*

### Drying time:

Dust dry:	approx. 24 hours.
Recoat after:	approx. 36 hours.
Min. processingtemperature:	5 °C.
Max. processingtemperature:	30 °C.

### Cleaning:

Clean tools with water.

*Pay attention! Pour used rags, cloths etc. over with water to avoid the risk of scalding.*

### Available quantities:

0,5L & 1L.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

**Available colors:**

Natural, Brown, Chocolate, Chalk White, Creamy White, Grey, Dark Grey & Black.

**Shelf life:**

Lacq RapidOil 2C can be stored in a cool dry for 24 months environment and in the original unopened packaging.

*Pay attention! If you do not need everything at once, do not mix the components together, because this hardens quickly and cannot be used afterwards.*

**Safety information:**

For detailed safety information, please consult the MSDS.

MSDS is available on [www.lacq.eu](http://www.lacq.eu).