



Fluxaf Pro

Fluxaf Pro is a paint stripper that quickly and powerfully removes water-based substances alkyd coatings, decorative plasters, anti-fouling, varnishes, glues and graffiti of almost all surfaces. Applicable to all types of wood and metal (except aluminium). None occur when stripping natural wood species discolouration. Plastics will generally be affected. It is recommended to test for a plastic substrate in advance inconspicuous place.

Removed:

- Waterborne and alkyl coatings
- Decorative plasters
- Anti-fouling
- Varnishing
- Glue
- Graffiti

Applicable on almost surfaces, such as:

- Wood species
- Metal (except aluminum)
- Plastic will generally be affected

Processing:

1. Before using Fluxaf Pro cover parts that do not need to be treated, so that these not be affected.
2. Remove the loose paint layers.
3. Apply Fluxaf Pro in a thick layer with a brush, roller or spatula. When using a we recommend a brush with natural bristles. Some plastic brushes are used affected by Fluxaf Pro. Nylon, on the other hand, is not affected.
4. Fluxaf Pro must be applied sufficiently thick so that this layer is thicker than the te remove paint layer.
5. Fluxaf Pro, applied to paint or plaster, will soak into the paint or plaster, that is when the paint or plaster is removed, so will the used paint remover be removed. After stripping, the paint or plaster will work with the stripper must be disposed of in accordance with the locally applicable guidelines. In practice there will then be no paint stripper should be spilled on the ground or other places.
6. Processing time on average from 15 to 45 minutes. Depending on the type of paint and the thickness of the paint layers, it may take up to several hours. Repeat treatment if necessary.
7. If space is created between the paint layers, a second treatment may be necessary, because the bottom paint layers are not affected.
8. High intensity sunlight and strong winds can cause the paint remover to dry too quickly. In these cases, apply more paint remover to the dried pieces.
9. Dissolved paint can be removed with a scraper, a brush or with a high pressure sprayer (60-90 ° C).
10. Wash the surface thoroughly with water.
11. It is very important with outer facades to start at the bottom and from there upwards to work.

Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.

Precautionary measures:

- Wearing proper safety gloves and goggles is recommended.
- Do not inhale the spray from the stripper.
- If Fluxaf Pro comes into contact with the skin or eyes, rinse thoroughly with water.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

- Fluxaf Pro is not for internal human use. If swallowed, consult a physician and take the safety data sheet.

Cleaning:

Clean tools with (warm) water.

Available quantities:

0,75L, 5L & 20L.

Shelf life:

Fluxaf Pro can be stored for up to 2 years between 5 ° C and 35 ° C in the original, unopened packaging.

Safety advice:

For extensive safety information, consult the MSDS.

MSDS can be downloaded at www.fluxaf.com.