



Fluxaf Super

Fluxaf Super is an absolutely safe, non-flammable, gel-like, pH neutral stripper, suitable for removing most types of coatings, glue and decorative plaster on almost all surfaces. Fluxaf Super stripper does not contain acids, bases, hazardous substances (such as NMP), paraffin or preservatives. Fluxaf Super can be used indoors and outdoors to about -8 °C.

Removed:

- Coatings
- Glue
- Decorative plasters

Applicable on almost all surfaces, such as:

- Concrete
- Natural stone
- Moist surfaces
- Mineral surfaces such as:
 - Wood
 - Metal
 - Alloy
 - Buyer
- Plastic will generally be affected.

Processing:

1. When using a brush, we recommend a brush with natural bristles. Some plastic brushes can react to Fluxaf Super Nylon, on the other hand, will not be affected.
2. Fluxaf Super is also easy to spray airless, use a nozzle with an opening from 0.21 "-0.31" and a spray angle of 40-50 °. Protective spraying during airless wear clothing and a suitable mask.
3. Fluxaf Super must be applied sufficiently thick so that this layer is thicker than the coating or decorative plaster to be removed.
4. Fluxaf Super applied to plaster or paint, will soak into the plaster or paint, so When the plaster or paint is removed, so will the used paint remover be removed. After stripping, the plaster or paint will go along with the stripper must be disposed of in accordance with the locally applicable guidelines.
5. Application time: Fluxaf Super is best left overnight for plastering It is customary to apply Fluxaf Super at the end of the afternoon the plaster and leave it on until the next morning. The plaster is then completely dissolved and easy to remove with a high pressure cleaner or scraper. Care make sure it is not removed too early, but let the product do its maximum work.
6. Processing time: with paint half an hour to 4 hours, depending on the type of paint and the thickness of the paint layers.
7. High intensity sunlight and strong winds can cause the paint remover to dry too quickly. In these cases, apply more paint remover to the dried pieces.
8. Dissolved paint or decorative plaster can be removed with a spatula, a brush or with a high pressure cleaner (60-90 ° C).
9. We recommend for exterior facades to start at the bottom and work your way up from there.

Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.

Precautionary measures:

- Use protective gloves and goggles.
- Do not inhale the spray from the stripper.
- If Fluxaf Super comes into contact with the skin or eyes, rinse thoroughly with water.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

- If swallowed, consult a physician and take safety

Cleaning:

Clean tools with (warm) water.

Available quantities:

Cans: 0.5L, 1L, 2.5L, 5L & 20L.

Steel drums: 60L & 200L.

IBC: 1000L.

Shelf life:

Fluxaf Super can be stored for up to 2 years between 5 ° C and 35 ° C in the original, unopened packaging.

Safety advice:

For extensive safety information, consult the MSDS.

MSDS can be downloaded at www.fluxaf.com.