

Lacq Emulsion Paint Ultra Matt

Lacq Emulsion Paint Ultra Matt is a complete solvent and plasticizer free allround wall paint for indoors. It is splash free, leaves a lot mild odor behind and is starter-free. In addition, it is an excellent fit product for renovation and new construction due to the long open time. Lacq Emulsion Paint Ultra Matt is very opaque and gives your interior a beautiful look, matte appearance. The interior is easily washable after treatment.

Applicable for he finishing of:

- Ceiling
- Brickwork
- Plaster
- Concrete
- Aerated concrete
- Plaster casts

Instructions:

- 1. Surface must be clean and dry, remove any loose parts and if necessary brush off the salt rash from the masonry.
- 2. Lacq Emulsion Paint Ultra Matt can be applied with a brush, brush, roller, air spray or airless (airless spray pressure 100-140 bar, spray nozzle 0.019-0.021 inch).
- 3. Finishing can be done with 1 or 2 layers, this of course depends on the color and the substrate.
- 4. In principle it is a ready-to-use product, if desired dilute with water.

Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per surface.

Application:

Apply with a brush, roller or airless.

Drying time:

Dust dry: approx. 1 hour. Recoatable after: approx. 6 hours.

Min. processing temperature: 10 °C. Max. processing temperature: 75 °C.

Cleaning:

Clean tools with water immediately after use.

Efficiency:

About 6-8 m² per liter.

Pay attention! Efficiency always depends on the structure, suction of the surface, the thickness of the layer, the tools used and the conditions of application.

Available quantities:

1L, 5L & 10L.

Available colors:

The product can be colored as desired.

Pay attention! With material on color, especially in dark colors, the technical properties of the product differ.

Shelf life:

Shelf life 12 months in unopened packaging. Store dry and frost-free in a well-closed packaging!

Safety information:

For detailed safety information, please consult the MSDS.

MSDS is available on www.lacq.eu.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.