

Lacq Interior Eggshell

Lacq Interior Eggshell is a professional, water-based interior lacquer. It has excellent adhesion and flow making it easy to apply. In addition, it is not yellowing, it has very good coverage and it is moisture-regulating. Lacq Interior Eggshell is quick-drying and low-odour, so it can be fully functional after 24 hours. After finishing it is easy to clean, wear and scratch resistant and will provide better resistance to hand grease and weak chemicals.

Application:

As a topcoat and finish for interior use on wood, stone and stony surfaces, plaster, concrete and hard plastics.

Applicable to interior work such as:

- Wood
- Stone and stony surfaces
- Plaster
- Concrete
- Hard plastics

Instructions:

- Stir well before use.
- Remove all loose paint layers; clean old intact paint layers with Fluxaf Pro-Clean.
- Sand well and make dust-free.
- Clean, prime and sand bare wood.
- Sand lightly between the base and topcoats. Fill and sand irregularities.
- Dilute with water if necessary.
- Application temperature between 7 ° C and 28 ° C. Do not process at a humidity above 85%.

Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.

Application:

Apply with brushes made of plastic bristles, paint rollers made of felt or microfiber or a paint sprayer.

Drying time:

Touch dry after: approx. 1 hour.
Tack free after: approx. 2 hours.
Recoatable after: approx. 8 hours.
Taxable after: approx. 24 hours.
Fully cured after: approx. 7 days.

Pay attention! At a lower temperature and higher humidity, the above times are longer. Do not process below 7 ° C air and substrate temperature and humidity above 85%.

Cleaning:

Clean tools with water immediately after use.

Efficiency:

Approx. 9-10 m² per liter. The yield depends on the application method, the quality of the substrate and the shape of the object.

Pay attention! Efficiency always depends on the structure, surface suction, film thickness, tools used and application conditions.

Available quantities:

0,5L, 1L & 2,5L.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

Available colors:

Colour can be requested as desired.

Pay attention! Dark colors in water-dilutable lacquers and wall paints, when wet (condensation & rain), can become a bit smudged due to moisture absorption. These stains disappear once the paint film has dried.

Shelf life:

Can be stored for at least 1 year in unopened packaging. Store cool, dry and frost-free. Good for use stir; close well after use.

Safety information:

For detailed safety information, please consult the MSDS. MSDS is available on www.lacq.eu.