



Lacq Multi Surface Primer

Lacq Multi Surface Primer is a high-quality, water-dilutable bonding primer that provides the right base before starting to finish. In addition, Lacq Multi Surface Primer has a positive influence on the durability of the subsequent layers, has a satin finish and is easy to apply.

Applicable for indoors and outdoors:

- Wood
- Metal
- Zinc
- Aluminum (sheet aluminum)
- Hard PVC

Instructions:

1. Stir well before use.
2. It is important to degrease the object in advance with Fluxaf Power-Clean or Fluxaf Pro-Clean.
3. Apply with a brush, roller or spray.
4. Close packaging tightly after use.

Pay attention! Always put on a sample first to see if you get the desired finish. This can differ per wood type.

Application:

Apply with a brush, roller or spray.

Drying time:

At approx. 23 °C. and 50% rel. humidity can be painted over with dispersion varnishes after 2 hours.

Pay attention! Leave synthetic resin coatings overnight.

Cleaning:

Clean tools with water immediately after use.

Efficiency:

About 10 m² per liter on a smooth surface.

The processing temperature: 9 - 30 °C
Relative humidity: maximum 85%

Pay attention! The yield depends on the application method, the quality of the substrate and the shape of the object.

Available quantities:

0,5L, 1L & 2,5L.

Available colors:

The product can be colored as desired.

Shelf life:

Can be stored for at least 1 year in unopened packaging. Store cool, dry and frost-free.

Safety information:

For detailed safety information, please consult the MSDS.
MSDS is available on www.lacq.eu.