



Lacq Douglas Oil

Lacq offers the right wood protection for every job! Lacq Douglas Oil is an authentic recipe based on various vegetable oils for the annual protection and maintenance of Douglas wood. Protects woods such as Douglas fir and larch for a long time against soiling or ageing, is very easy to apply and preserves the natural wood colour.

Applicable To:

- Sheds
- Fences
- Other garden wood

Suitable For:

- Douglas wood
- Larch wood
- Other softwood species

Application On Untreated Wood:

1. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Remove all existing paint and stain layers first.
2. First clean greyed wood with [Lacq Wood Degreaser](#).
3. Clean with [Fluxaf Pro-Clean](#).
4. Stir the contents thoroughly.
5. Use a flat brush or roller suitable for solvent-based paint.
6. For a good finish, apply the oil in a lengthways direction of the wood. Work in zones or plank by plank.
7. Allow the oil to penetrate for 10-15 minutes.
8. To prevent film thickness build-up, after 15 minutes, scrub out excess oil with a lint-free cloth until the wooden surface feels dry to the touch.
9. If there are still 'chapped' areas after drying, repeat the treatment.
10. Avoid layer thickness build-up: If you do not scrub out the excess oil, shiny and/or sticky spots may appear on the wood.

Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance, and intensity of load. Always do a test area first to see if you get the desired finish and this will vary on different wood.

Surface Maintenance:

To make best use of the product, the surface should be cleaned and maintained annually. The surface can be cleaned by gently wiping it. Use a damp cleaning cloth or soft sponge for this purpose. Rough brushing and strong detergents should be avoided.

Tools:

Flat brush or roller suitable for solvent-based paint and a lint-free cloth.

Coverage:

Approximately 10-15 m² per litre.

Coverage always depends on the structure, porosity of the wood, layer thickness, the tools used and application conditions.

Drying Time:

Drying times depend on the applied layer and ambient temperature. Optimal conditions are 20 °C.

Dust-dry:	Approx. 1 hour
Paintable:	Approx. 9 hours
Min. working temperature:	9 °C.
Max. processing temperature:	25 °C.

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

Tool Cleaning:

Clean tools with white spirit.

Available Quantities:

750 ml.

Finish:

Matt.

Available Colours:

Natural.

Please note! The type of wood and the number of coats applied may influence the colour result. We therefore recommend always putting on a test piece first to assess the result.

Shelf Life:

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

Safety Advice:

Keep out of the reach of children. For detailed safety information, refer to the MSDS. MSDS can be downloaded at www.lacq.eu.

Customised advice:

For any advice, please contact the technical team on 0344 633 336.