



Lacq Wood Tar

Lacq offers the right wood protection for every job! Lacq Wood Tar is a substitute for carbolineum based on vegetable raw materials and has been specially developed, among other things, for wooden surfaces already treated with tar products. The characteristic appearance is preserved by the black/brown coating while providing good protection. Penetrates deep into the wood, is weather-resistant, moisture-regulating, and easy to apply. It will protect the wood for up to 5 years!

Applicable To:

- Sheds
- Fences
- Sheds
- Mills
- Batten boards
- Facade parts

Suitable For:

- Wood previously treated with a tar product
- Larch wood
- Spruce wood
- Pine wood
- Scaffolding wood
- Untreated wood
- Treated wood

Features:

- UV resistant
- Does not leaf
- Ready to use
- Water-repellent
- Strongly impregnating

Application On Untreated Wood:

1. The surface must be clean, dry and sound. Remove dirt, dust, mould, algae and moss growth and loose parts. Sanding is not necessary, only when a smooth result is desired.
2. Clean with [Fluxaf Pro-Clean](#).
3. Stir the contents thoroughly.
Use a flat brush, buckshot or roller. Apply in the longitudinal direction of the wood grain for a good finish.
4. Apply first coat.
5. The second coat can only be applied after complete drying of first coat.
6. We recommend applying two coats to untreated wood.
7. The applied coat slowly becomes evenly mattified over time.

Duration of wood protection depends on the quality of the wood, correct pre-treatment, execution of painting, maintenance, and intensity of load. Always do a test area first to see if you get the desired finish and this will vary on different wood.

Surface Maintenance:

To make best use of the paintwork, the surface should be cleaned and maintained annually. The surface can be cleaned by gently wiping it. Use a damp cleaning cloth or soft sponge for this purpose. Rough brushing and strong detergents should be avoided.

Tools:

Flat brush, buckshot or roller suitable for solvent-based paint.

Coverage:

The technical information and specifications contained in this data sheet are based on careful investigations and years of practical experience and are provided to the best of our knowledge. The circumstances under which this product works in practice used may cause many variables. This allows VLIEGENTHART B.V. not be held responsible for possible deviations.

Approximately 10-12 m² per litre.

Coverage always depends on the structure, suction of the wood, layer thickness, the tools used and application conditions.

Drying time:

Dust-dry:	Approx. 4 hour
Paintable:	Approx. 8 hours
Min. working temperature:	5 °C.
Max. processing temperature:	30 °C.

Tool Cleaning:

Clean tools with white spirit.

Available Quantities:

750 ml & 2.5 litres.

Finish:

Matt.

Available Colours:

Brown & Black.

Please note! The type of wood and the number of coats applied may influence the colour result. We therefore recommend always putting on a test area first to assess the result.

Shelf Life:

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

Safety Advice:

Keep out of the reach of children. For detailed safety information, refer to the MSDS. MSDS can be downloaded at www.lacq.eu.

Customised advice:

For any advice, please contact the technical team on 0344 633 336.