



**VLIEGENTHART**  
SINCE 1839

## Safety data sheet



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Lacq Wood Tar brown  
**Other means of identification:**  
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**  
Relevant uses: Paints and varnishes  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**  
Vliegenthart B.V.  
Zuiderhavenweg 42  
4000 HH Tiel - Gelderland - Netherlands  
Phone: +31 344 633336  
info@vliegenthart.com
- 1.4 Emergency telephone number:** +31 (0) 344 633336

#### SECTION 2: HAZARDS IDENTIFICATION \*\*

- 2.1 Classification of the substance or mixture:**  
**CLP Regulation (EC) No 1272/2008:**  
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.  
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411  
Skin Irrit. 2: Skin irritation, Category 2, H315  
Skin Sens. 1: Sensitisation, skin, Category 1, H317  
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**  
**CLP Regulation (EC) No 1272/2008:**  
**Warning**
-  
- Hazard statements:**  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**  
P101: If medical advice is needed, have product container or label at hand.  
P102: Keep out of reach of children.  
P264: Wash thoroughly after handling.  
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
P501: Dispose of contents/container according to the separated collection system used in your municipality.
- Substances that contribute to the classification**  
Kerosine (petroleum), hydrodesulfurized (CAS: 64742-81-0); Rosin (CAS: 8050-09-7)
- 2.3 Other hazards:**  
Product fails to meet PBT/vPvB criteria  
Endocrine-disrupting properties: The product fails to meet the criteria.

\*\* Changes with regards to the previous version

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**VLIEGENTHART**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

##### 3.1 Substance:

Non-applicable

##### 3.2 Mixture:

**Chemical description:** Mixture based on hydrocarbons and additives

##### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 64742-81-0 EC: 265-184-9 Index: 649-423-00-8 REACH: 01-2119462828-25-XXXX	<b>Kerosine (petroleum), hydrodesulfurized</b> <sup>1</sup> Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	Self-classified 25 - <50 %
CAS: Non-applicable EC: 918-481-9 Index: Non-applicable REACH: 01-2119457273-39-XXXX	<b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics</b> <sup>1</sup> Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger	Self-classified 1 - <3 %
CAS: 8050-09-7 EC: 232-475-7 Index: 650-015-00-7 REACH: 01-2119480418-32-XXXX	<b>Rosin</b> <sup>1</sup> Regulation 1272/2008 Skin Sens. 1: H317 - Warning	ATP CLP00 1 - <3 %
CAS: 27253-29-8 EC: 248-370-4 Index: Non-applicable REACH: 01-2119978981-18-XXXX	<b>Zinc neodecanoate</b> <sup>1</sup> Regulation 1272/2008 Aquatic Chronic 3: H412	Self-classified 1 - <3 %
CAS: 27253-32-3 EC: 248-374-6 Index: Non-applicable REACH: 01-2120796051-56-XXXX	<b>Manganese neodecanoate</b> <sup>1</sup> Regulation 1272/2008 STOT RE 2: H373 - Warning	Self-classified 1 - <3 %
CAS: 15956-58-8 EC: 240-085-3 Index: 607-230-00-6 REACH: 01-2119979087-23-XXXX	<b>2-ethylhexanoic acid, manganese salt</b> <sup>1</sup> Regulation 1272/2008 Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Repr. 2: H361d; STOT RE 2: H373 - Warning	Self-classified 0,15 - <1 %
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	<b>Dipropylene Glycol Methyl Ether</b> <sup>2</sup> Regulation 1272/2008	Not classified 0,1 - <0,15 %
CAS: 149-57-5 EC: 205-743-6 Index: 607-230-00-6 REACH: 01-2119488942-23-XXXX	<b>2-ethylhexanoic acid</b> <sup>1</sup> Regulation 1272/2008 Repr. 1B: H360D - Danger	ATP ATP18 0,1 - <0,15 %
CAS: 111-76-2 EC: 203-905-0 Index: 603-014-00-0 REACH: 01-2119475108-36-XXXX	<b>2-butoxyethanol</b> <sup>2</sup> Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning	Self-classified <0,1 %

<sup>1</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

<sup>2</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

#### SECTION 4: FIRST AID MEASURES

##### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

- CONTINUED ON NEXT PAGE -



**VLIEGHART**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 4: FIRST AID MEASURES (continued)

##### **By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

##### **By eye contact:**

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

##### **By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### **4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

#### **4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

#### SECTION 5: FIREFIGHTING MEASURES

##### **5.1 Extinguishing media:**

###### **Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

###### **Unsuitable extinguishing media:**

Non-applicable

##### **5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

##### **5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

###### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

##### **6.1 Personal precautions, protective equipment and emergency procedures:**

###### **For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

###### **For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

##### **6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

##### **6.3 Methods and material for containment and cleaning up:**

- CONTINUED ON NEXT PAGE -



**V.L.I.E.G.H.A.R.T.**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

##### 6.4 Reference to other sections:

See sections 8 and 13.

#### SECTION 7: HANDLING AND STORAGE

##### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

##### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

##### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	20 ppm	98 mg/m <sup>3</sup>
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	IOELV (STEL)	50 ppm	246 mg/m <sup>3</sup>
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	IOELV (8h)	50 ppm	308 mg/m <sup>3</sup>
	IOELV (STEL)		

##### DNEL (Workers):

- CONTINUED ON NEXT PAGE -



**Lacq Wood Tar brown**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Rosin CAS: 8050-09-7 EC: 232-475-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,131 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>
Zinc neodecanoate CAS: 27253-29-8 EC: 248-370-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	7,41 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	22,04 mg/m <sup>3</sup>	Non-applicable
2-ethylhexanoic acid, manganese salt CAS: 15956-58-8 EC: 240-085-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	5,91 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1,19 mg/m <sup>3</sup>	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	308 mg/m <sup>3</sup>	Non-applicable
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	14 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	89 mg/kg	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	1091 mg/m <sup>3</sup>	246 mg/m <sup>3</sup>	98 mg/m <sup>3</sup>	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Rosin CAS: 8050-09-7 EC: 232-475-7	Oral	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Zinc neodecanoate CAS: 27253-29-8 EC: 248-370-4	Oral	Non-applicable	Non-applicable	1,88 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,06 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	6,52 mg/m <sup>3</sup>	Non-applicable
2-ethylhexanoic acid, manganese salt CAS: 15956-58-8 EC: 240-085-3	Oral	Non-applicable	Non-applicable	4,1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,96 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,26 mg/m <sup>3</sup>	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	37,2 mg/m <sup>3</sup>	Non-applicable
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	Oral	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	3,5 mg/m <sup>3</sup>	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Oral	Non-applicable	Non-applicable	6,3 mg/kg	Non-applicable
	Dermal	89 mg/kg	Non-applicable	75 mg/kg	Non-applicable
	Inhalation	426 mg/m <sup>3</sup>	147 mg/m <sup>3</sup>	59 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification				
Rosin CAS: 8050-09-7 EC: 232-475-7	STP	1000 mg/L	Fresh water	0,002 mg/L
	Soil	0 mg/kg	Marine water	0 mg/L
	Intermittent	0,016 mg/L	Sediment (Fresh water)	0,007 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,001 mg/kg
Zinc neodecanoate CAS: 27253-29-8 EC: 248-370-4	STP	Non-applicable	Fresh water	0,478 mg/L
	Soil	Non-applicable	Marine water	0,048 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable
	Oral	0,017 g/kg	Sediment (Marine water)	Non-applicable

- CONTINUED ON NEXT PAGE -



**Lacq Wood Tar brown**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification				
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L
	Soil	2,74 mg/kg	Marine water	1,9 mg/L
	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	STP	71,7 mg/L	Fresh water	0,398 mg/L
	Soil	0,712 mg/kg	Marine water	0,04 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	4,74 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,474 mg/kg
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	STP	463 mg/L	Fresh water	8,8 mg/L
	Soil	2,33 mg/kg	Marine water	0,88 mg/L
	Intermittent	26,4 mg/L	Sediment (Fresh water)	34,6 mg/kg
	Oral	0,02 g/kg	Sediment (Marine water)	3,46 mg/kg

**8.2 Exposure controls:**

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.11 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

- CONTINUED ON NEXT PAGE -



**VLIEGENTHART**  
SINCE 1839



## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

##### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

##### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

##### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	33,17 % weight
V.O.C. density at 25 °C:	303,51 kg/m <sup>3</sup> (303,51 g/L)
Average carbon number:	11,97
Average molecular weight:	179,24 g/mol

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

##### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

##### Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	According to the markings on the package, Black
Odour:	Not available
Odour threshold:	Non-applicable *

##### Volatility:

Boiling point at atmospheric pressure:	>200 °C
Vapour pressure at 25 °C:	>543 Pa
Vapour pressure at 50 °C:	Non-applicable *
Evaporation rate at 25 °C:	Non-applicable *

##### Product description:

Density at 25 °C:	915 kg/m <sup>3</sup>
Relative density at 25 °C:	0,898
Dynamic viscosity at 25 °C:	100 cP
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 °C:	Non-applicable *
Partition coefficient n-octanol/water 25 °C:	Non-applicable *
Solubility in water at 25 °C:	Non-applicable *
Solubility properties:	Insoluble in water
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**VLEIEGHART**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

##### Flammability:

Flash Point:	>100 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	>250 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

##### Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

#### 9.2 Other information:

##### Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

##### Other safety characteristics:

Surface tension at 25 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

#### SECTION 10: STABILITY AND REACTIVITY

##### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

##### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

##### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

##### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

##### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

##### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds

#### SECTION 11: TOXICOLOGICAL INFORMATION \*\*

##### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -





## Lacq Wood Tar brown

### SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

##### A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

##### B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

##### C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

##### D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: 2-butoxyethanol (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

##### E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

##### F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

##### G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

##### H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

#### Other information:

Non-applicable

#### Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Kerosine (petroleum), hydrodesulfurized CAS: 64742-81-0 EC: 265-184-9	5000 mg/kg	2100 mg/kg	Rat
	Non-applicable		Rabbit
	Non-applicable		
Rosin CAS: 8050-09-7 EC: 232-475-7	4100 mg/kg	Non-applicable	Rat
	Non-applicable		
	Non-applicable		

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**VLIEGHART**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Manganese neodecanoate CAS: 27253-32-3 EC: 248-374-6	2066 mg/kg	Non-applicable	Rat
2-ethylhexanoic acid, manganese salt CAS: 15956-58-8 EC: 240-085-3	2150 mg/kg	Non-applicable	Rat
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	>5000 mg/kg	9510 mg/kg	Rat Rabbit
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	3000 mg/kg	Non-applicable	Rat
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	1200 mg/kg	3000 mg/kg	Rat Rabbit
	3 mg/L		

#### 11.2 Information on other hazards:

##### Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

##### Other information

Non-applicable

\*\* Changes with regards to the previous version

#### SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

#### 12.1 Toxicity:

##### Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
Kerosine (petroleum), hydrodesulfurized CAS: 64742-81-0 EC: 265-184-9	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Rosin CAS: 8050-09-7 EC: 232-475-7	LC50	150 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	238 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	185 mg/L (72 h)	Selenastrum capricornutum	Algae
Zinc neodecanoate CAS: 27253-29-8 EC: 248-370-4	LC50	>10 - 100 mg/L (96 h)		Fish
	EC50	>10 - 100 mg/L (48 h)		Crustacean
	EC50	>10 - 100 mg/L (72 h)		Algae
2-ethylhexanoic acid, manganese salt CAS: 15956-58-8 EC: 240-085-3	LC50	270 mg/L (96 h)	N/A	Fish
	EC50	3 mg/L (48 h)	N/A	Crustacean
	EC50	61 mg/L (72 h)	N/A	Algae
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	LC50	180 mg/L (48 h)	Salmo gairdneri	Fish
	EC50	116,6 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	61 mg/L (72 h)	Scenedesmus subspicatus	Algae

##### Chronic toxicity:

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**Lacq Wood Tar brown**

**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Concentration		Species	Genus
Zinc neodecanoate	NOEC	0,199 mg/L	Oncorhynchus mykiss	Fish
CAS: 27253-29-8 EC: 248-370-4	NOEC	0,9 mg/L	Mya arenaria	Crustacean
Manganese neodecanoate	NOEC	Non-applicable		
CAS: 27253-32-3 EC: 248-374-6	NOEC	0,02 mg/L	Crassostrea gigas	Crustacean
2-ethylhexanoic acid, manganese salt	NOEC	0,6 mg/L	Oncorhynchus mykiss	Fish
CAS: 15956-58-8 EC: 240-085-3	NOEC	25 mg/L	Daphnia magna	Crustacean
Dipropylene Glycol Methyl Ether	NOEC	Non-applicable		
CAS: 34590-94-8 EC: 252-104-2	NOEC	0,5 mg/L	Daphnia magna	Crustacean
2-ethylhexanoic acid	NOEC	Non-applicable		
CAS: 149-57-5 EC: 205-743-6	NOEC	18 mg/L	Daphnia magna	Crustacean
2-butoxyethanol	NOEC	100 mg/L	Danio rerio	Fish
CAS: 111-76-2 EC: 203-905-0	NOEC	100 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

**Substance-specific information:**

Identification	Degradability		Biodegradability	
Rosin CAS: 8050-09-7 EC: 232-475-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	32 %
Manganese neodecanoate CAS: 27253-32-3 EC: 248-374-6	BOD5	Non-applicable	Concentration	40 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	11 %
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BOD5	Non-applicable	Concentration	Non-applicable
	COD	0 g O2/g	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	73 %
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	BOD5	Non-applicable	Concentration	Non-applicable
	COD	2,11 g O2/g	Period	Non-applicable
	BOD5/COD	Non-applicable	% Biodegradable	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BOD5	0,71 g O2/g	Concentration	100 mg/L
	COD	2,2 g O2/g	Period	14 days
	BOD5/COD	0,32	% Biodegradable	96 %

**12.3 Bioaccumulative potential:**

**Substance-specific information:**

Identification	Bioaccumulation potential	
Kerosine (petroleum), hydrodesulfurized CAS: 64742-81-0 EC: 265-184-9	BCF	130
	Pow Log	3.3
	Potential	High
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low
2-ethylhexanoic acid CAS: 149-57-5 EC: 205-743-6	BCF	3
	Pow Log	2.64
	Potential	Low
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	BCF	3
	Pow Log	0.83
	Potential	Low

**12.4 Mobility in soil:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**Lacq Wood Tar brown**

**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Absorption/desorption		Volatility	
Zinc neodecanoate CAS: 27253-29-8 EC: 248-370-4	Koc	121	Henry	5,4E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	No
Manganese neodecanoate CAS: 27253-32-3 EC: 248-374-6	Koc	121	Henry	Non-applicable
	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
2-butoxyethanol CAS: 111-76-2 EC: 203-905-0	Koc	8	Henry	1,621E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	2,729E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Endocrine disrupting properties:**

Endocrine-disrupting properties: The product fails to meet the criteria.

**12.7 Other adverse effects:**

Not described

\*\* Changes with regards to the previous version

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION \*\***

**Transport of dangerous goods by land:**

With regard to ADR 2021 and RID 2021:

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**VLEIENDE WERK**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 14: TRANSPORT INFORMATION \*\* (continued)



- 14.1 UN number or ID number:** UN3082
- 14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-ethylhexanoic acid, manganese salt; Kerosine (petroleum), hydrodesulfurized)
- 14.3 Transport hazard class(es):** 9  
Labels: 9
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Special regulations: 274, 335, 375, 601  
Tunnel restriction code: -  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

#### Transport of dangerous goods by sea:

With regard to IMDG 40-20:

- 14.1 UN number or ID number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable  
Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**  
Special regulations: Non-applicable  
EmS Codes:  
Physico-Chemical properties: see section 9  
Limited quantities: Non-applicable  
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

- 14.1 UN number or ID number:** Non-applicable
- 14.2 UN proper shipping name:** Non-applicable
- 14.3 Transport hazard class(es):** Non-applicable  
Labels: Non-applicable
- 14.4 Packing group:** Non-applicable
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

\*\* Changes with regards to the previous version

#### SECTION 15: REGULATORY INFORMATION

##### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

- CONTINUED ON NEXT PAGE -



**VLEIEGHART**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 15: REGULATORY INFORMATION (continued)

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Non-applicable  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

##### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

##### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

##### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

##### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

#### SECTION 16: OTHER INFORMATION \*\*

##### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

##### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
  - Zinc neodecanoate (27253-29-8)
  - Manganese neodecanoate (27253-32-3)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Pictograms
- Hazard statements

TRANSPORT INFORMATION (SECTION 14):

- UN number
- Packing group

##### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.  
H336: May cause drowsiness or dizziness.  
H411: Toxic to aquatic life with long lasting effects.  
H317: May cause an allergic skin reaction.

##### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

##### CLP Regulation (EC) No 1272/2008:

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**VLEIENHART**  
SINCE 1839

## Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### Lacq Wood Tar brown

#### SECTION 16: OTHER INFORMATION \*\* (continued)

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Repr. 1B: H360D - May damage the unborn child.  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

#### **Classification procedure:**

Skin Irrit. 2: Calculation method  
STOT SE 3: Calculation method  
Aquatic Chronic 2: Calculation method  
Skin Sens. 1: Calculation method

#### **Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### **Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
LogPOW: Octanolwater partition coefficient  
Koc: Partition coefficient of organic carbon  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

*\*\* Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -