



Lacq Invisible

Lacq offers the right wood protection for every job! Lacq Invisible is an extremely strong, ultra-matt lacquer specially developed for hardwood floors and parquet. This urethane acrylate lacquer offers extremely high wear resistance and is also suitable for wooden furniture. Thanks to its water-based formula, Lacq Invisible is low-odour, easy to apply and ideal for floors subject to heavy use. The varnish prevents overlap and brush marks and ensures a truly natural look.

Suitable for use on wood:

- Floors
- Furniture
- Stairs
- Other interior wood

Application:

Untreated wood:

1. Degrease the floor with Fluxaf Cleaner & Degreaser. Degrease tropical woods such as teak, wenge, etc. with thinner.
2. Sand the surface according to the rules for the wood. Use 120-150 grit sandpaper for this. After sanding, vacuum thoroughly and remove all dust residue.
3. Stir the product well.
4. The product can be applied with a brush or roller.
5. We recommend applying 3 coats for maximum protection.
6. Sand in between coats with P220 or P320 grit sandpaper.
7. Always ensure adequate ventilation.

Treated wood:

1. First thoroughly remove all old varnish, wax or oil layers, as these can have a negative effect on the adhesion and quality of Lacq Invisible. This can be done with the appropriate sanding machines and/or cleaning agents.
2. Sand the surface according to the grain of the wood. Use P120 - P150 grit for this. After sanding, vacuum thoroughly and remove all dust residues.
3. Stir the product well.
4. The product can be applied with a brush or roller.
5. We recommend applying 3 coats for maximum protection.
6. Sand in between coats with P220 or P240 grit.
7. Always ensure adequate ventilation.

Please note! Always test a small area first to see if you get the desired finish. This can vary depending on the type of wood.

Coverage:

Approximately 12 m² per litre.

Please note! Coverage always depends on the structure and absorbency of the wood, the layer thickness, the tools used and the application conditions.

Drying time:

Dust dry:	approx. 1,5 hours.
Recoat after:	approx. 2 hours.
Minimum processing temperature:	10 °C.
Maximum processing temperature:	25 °C.

Cleaning:

Clean tools with water.

Technical characteristics:

Moisture-regulating effect: No
Substance: Liquid

Available quantities:

750 ml & 2.5 litres.

Available colours:

Colourless.

Shelf life:

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

Safety advice:

Keep out of the reach of children. For detailed safety information, refer to the MSDS.
MSDS can be downloaded at www.lacq.nl.