



Lacq Stair Varnish Anti-slip

Lacq offers the right wood protection for every job! Lacq Stair Varnish Anti-slip is a water-based, transparent varnish specially developed for indoor wooden stairs. The varnish is wear-resistant, quick-drying and has an anti-slip formula that reduces the risk of slipping. Ideal for surfaces subject to daily wear and tear, such as stair treads and risers.

Suitable for indoor wooden stairs:

- Stair treads
- Riser boards
- Handrails
- Other wooden stair components

Application:

1. Ensure the area is dry, clean and well ventilated.
2. Remove dirt, dust and grease from the surface. Lightly sand untreated or old wood (180–220 grit) and remove dust.
3. Stir the varnish well before use.
4. Apply Lacq Stair Varnish evenly with a brush or roller, in the direction of the wood grain.
5. Allow the first coat to dry for approx. 6 hours (depending on temperature and humidity).
6. Apply a second coat in the same way.
7. Allow to dry thoroughly before using the stairs.

Please note! Always test a small area first to see if you get the desired finish. This can vary depending on the type of wood. Due to its anti-slip properties, this product has a high viscosity. Its thicker consistency is an intentional product characteristic and does not indicate a quality defect.

Coverage:

Approximately 10 m² per litre.

Please note! Coverage always depends on the structure and absorbency of the wood, the layer thickness, the tools used and the application conditions.

Drying time:

Dust dry:	approx. 1 hour.
Recoat after:	approx. 6 hours.
Min. processing temperature:	10 °C.
Max. processing temperature:	25 °C.

Cleaning:

Clean tools with white spirit.

Available quantities:

750 ml & 2,5 litres.

Available colours:

Colourless, White and mixable to colour.

Shelf life:

Close airtight after use and turn over briefly to fill the rim for a good seal. Store 2 years in original unopened packaging, frost-free, in a dry place (temperature between 5°C and 35°C).

Safety advice:

Keep out of the reach of children. For detailed safety information, refer to the MSDS.

MSDS can be downloaded at www.lacq.nl.